

UA™ 35T II Utility Amplifier



SPECIFICATIONS

Output Power:

35 watts RMS

Power Bandwidth:

50 Hz-20 kHz, .8% THD Mic
50 Hz-20 kHz, .6% THD AUX

Frequency Response:

50 Hz-20 kHz +0, -2 dB
50 Hz-20 kHz +0, -2 dB Mic/Page

THD (1 kHz):

Aux <.05%
Mic <.2%
Page <.2%

S/N Ratio (22 kHz BW):

Tone controls flat/input control max:
85 dB Aux
58 dB Mic/Page

Tone Controls:

Bass ± 10 dB @ 100 Hz
Treble ±10 dB @ 10 kHz

Inputs:

AUX Input: Dual RCA phono jacks, summed
Mic/Page Input: Screw terminal input switchable between mic/page

Input Sensitivity:

AUX Input: 100 mV @ 10K
Mic Input: 1 mV @ 1K
Page Input: 120 mV @ 5K

Outputs:

4 ohms, 8 ohms, 600 ohms, 25 V, 70 V

Output Regulation:

Less than 0.5 dB, no load to full load

Controls:

1 AUX input gain control, 1 mic/page gain control, 1 bass control, 1 treble control, 1 mic/page select switch

Indicators:

Power LED

Protection:

Built-in, with AC line fuse

Power Consumption:

120 volts AC, 60 Hz, 100 watts

Dimensions:

4.25" H x 8.25" W x 13.625" D

Weight:

11.5 pounds

Color:

Gray

Other Features:

Mic/Page input has precedence over the AUX input (defeatable)

FEATURES

- 35 watts into 4 ohms
- Mic/page inputs (screw terminals)
- Mic/page select switch
- Dedicated program input (screw terminals and RCA jacks)
- Bass and treble controls
- Mic/page level controls
- Direct 4 ohm output (screw terminal)
- Completely isolated 8 ohm, 600 ohm, 25 volt and 70 volt outputs (screw terminals)
- Shelf-top or wall-mountable chassis

DESCRIPTION

The UA™ 35T II is a high quality utility amplifier ideally suited for varying installation requirements. It produces 35 watts into 4 and 8 ohm direct connections plus a

broad range of line amplification.

Level controls are provided for mic/page and AUX. The AUX input is accessible via screw terminals or RCA jacks. Bass and treble controls are functional on the total system (mic/page/AUX). When a signal is present at the mix/page input, the AUX input is muted. This feature is internally defeated when required.

Twenty-five and seventy volt line output capability is standard equipment, and the unit is packaged for shelf or wall mounting convenience. The user-friendly control layout, coupled with state-of-the-art circuit design, ensures reliable long-term operation and smooth trouble-free installation.

WALL OR SHELF MOUNTING

The UA 35T II can be mounted on a vertical or horizontal surface using the brackets formed on the bottom panel. For mounting on a wooden or paneled surface, use No. 6 x 1/2" or larger wood screws. For mounting onto a masonry or drywall type surface, use fasteners that are designed for this purpose.

UA 35T II ARCHITECTURAL AND ENGINEERING SPECIFICATIONS

The mixer amplifier shall have one switchable microphone/paging channel and one dedicated auxiliary channel. The mic/page input will be transformer balanced and will have the capability to automatically mute the AUX input. The master section shall include

two EQ controls providing 10 dB of boost or cut at 100 Hz and 10 kHz. The unit shall be packaged in a rugged metal chassis 4.25" tall by 8.25" wide by 13.625" deep. Half-inch mounting flanges shall be provided on each side. The unit shall operate from 120 volts AC, 60 Hz power. The internal amplifier shall be capable of delivering 35 watts RMS into 4 ohms and 8

ohms as well as providing 25 volt and 70 volt line outputs. The unit shall be capable of delivering rated power from 50 Hz to 20 kHz +0, -2 dB into 4 ohms at its 4 ohms output at less than .05% distortion with system hum and noise at least 85 dB below rated power (Aux Input). The unit shall be a Peavey Architectural Acoustics Division model UA 35T II.

LIMITED WARRANTY

Peavey Electronics Corporation warrants to the original purchaser of this new Architectural Acoustics product that it is free from defects in material and workmanship. If within one (1) year from date of purchase a properly installed product proves to be defective and Peavey is notified, Peavey will repair or replace it at no charge. (Note: Batteries and patch cords not covered.) "Original purchaser" means the customer for whom the product is originally installed.

Damage resulting from improper installation, interconnection of a unit or system of another manufacturer, accident or unreasonable use, neglect or any other cause not arising from defects in material and workmanship is not covered by this warranty. The warranty is valid only as to products purchased and installed in the United States.

THIS LIMITED WARRANTY IS IN LIEU OF ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE. UNDER NO CIRCUMSTANCES WILL PEAVEY BE LIABLE FOR ANY LOST PROFITS, LOST SAVINGS, INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT, EVEN IF PEAVEY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. THIS LIMITED WARRANTY IS THE ONLY EXPRESSED WARRANTY ON THIS PRODUCT, AND NO OTHER STATEMENT, REPRESENTATION, WARRANTY, OR AGREEMENT BY ANY PERSON SHALL BE VALID OR BINDING UPON PEAVEY.

Peavey's liability to the original purchaser for damages for any cause whatsoever and regardless of the form of action, is limited to the actual damages up to the greater of Five Hundred Dollars (\$500) or an amount equal to the purchase price of the product that caused the damage or that is the subject of or is directly related to the cause of action. This limitation of liability will not apply to claims for personal injury or damage to real property or tangible personal property allegedly caused by Peavey's negligence. For information on service under this warranty, call a Peavey customer service representative at (601) 483-5376.



Features and specifications subject to change without notice.

Peavey Electronics Corporation / 711 A Street / Meridian, MS 39301 / U.S.A. / (601) 483-5376 / Fax 486-1154

