



PVM™ 45ir

DYNAMIC MICROPHONE

Thank you for choosing the Peavey PVM 45ir. The PVM 45ir is dynamic and utilizes a super-cardioid pickup pattern, one of the most popular patterns in the industry for use with acoustic instruments and vocals. The slightly narrow on-axis pickup range affords the vocal user less bleed-over from other instruments or vocals. The null point of the PVM 45ir is located typically 15 dB less sensitive than the on-axis response. This helps reduce feedback from stage monitors and background noise. The PVM 45ir performs great on stage and in the recording studio.


- Super-cardioid pickup pattern
- Excellent acoustic instrument and vocal microphone
- Rugged construction
- Rubberized finish reduces handling noise
- Carrying pouch, mic clip and stand adapter
- XLR-to-XLR mic cable

SPECIFICATIONS:


Type:	Dynamic
Pickup Pattern:	Super-cardioid
Frequency Response:	50~1800 Hz
Sensitivity:	-56 dBv/pa
Output Impedance:	200 Ohm
Connector:	XLR 3 pins silver plated
Dimensions:	38 (max.) x 140 mm
Net Weight:	295 g



Frequency Response



Pick-Up Pattern



Accessories Included



Peavey Electronics Corporation • 5022 Hartley Peavey Drive • Meridian, MS 39305
Phone: (601) 483-5365 • Fax: (601) 486-1278 • www.peavey.com

Logo referenced in Directive 2002/96/EC Annex IV (OJ/L)37/38, 13.02.03 and defined in EN 50419: 2005
The bar is the symbol for marking of new waste and is applied only to equipment manufactured after 13 August 2005