

PRO 12

OVERVIEW

PRO 12

FEATURES

- Impedance: 8 Ohms
- Power capacity: 800 W Peak 400 W Program 200 W Continuous
- Sensitivity: 94.3 dB / 1 W 1 m
- Usable freq. range: 50 Hz ~ 4 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 2.375" / 60.3 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 9.7 lbs. / 4.4 kg
- Znom (ohms) 8
- Revc (ohms) 6.00
- Sd (Square Meters) 0.053
- BL (T/M) 12.36
- Fo (Hz) 48.4
- Vas (liters) 86.4
- Cms (uM/N) 219.7
- Mms (gm) 49.10
- Qms 3.84
- Qes 0.588
- Qts 0.510
- Xmax (mm) 2.5
- Le (mH) 0.72
- SPL (1W 1m) 94.3
- No (%) 1.73%
- Vd (cu. in. / ml) 16.2 / 266
- Pmax (Watts pgm.) 400
- Disp (cu. in. / ml) 73 / 1192
- 12"
- Weight Unpacked: 9.92 lb(4.5 kg)
- Weight Packed: 12.13 lb(5.5 kg)
- Width Packed: 13.125"(33.3375 cm)
- Height Packed: 14"(35.56 cm)
- Depth Packed: 6.75"(17.145 cm)