

PRO 15

OVERVIEW

PRO 15

FEATURES

- Impedance: 8 Ohms
- Power capacity: 800 W Peak 400 W Program 200 W Continuous
- Sensitivity: 96.4 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 3 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 2.5" / 63 mm
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- Net weight lb. / kg: 10.4 lbs. / 4.7 kg
- Znom (ohms) 8
- Revc (ohms) 6.00
- Sd (Square Meters) 0.086
- BL (T/M) 13.35
- Fo (Hz) 34.4
- Vas (liters) 331.6
- Cms (uM/N) 324.6
- Mms (gm) 66.50
- Qms 3.58
- Qes 0.482
- Qts 0.425
- Xmax (mm) 2.5
- Le (mH) 0.74
- SPL (1W 1m) 96.4
- No (%) 2.40%
- Vd (cu. in. / ml) 26.1 / 428
- Pmax (Watts pgm.) 400
- Disp (cu. in. / ml) 131 / 2154
- 15"
- Weight Unpacked: 13.78 lb(6.25 kg)
- Weight Packed: 15.98 lb(7.25 kg)
- Width Packed: 16.25"(41.275 cm)
- Height Packed: 17.25"(43.815 cm)
- Depth Packed: 7.5"(19.05 cm)