

# 1502-8 BW™

## OVERVIEW

1502-8 BW™

## FEATURES

- Impedance: 8 Ohms
- Power capacity: 1400 W Peak 700 W Program 350 W Continuous
- Sensitivity: 98.9 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 17 lbs. / 7.7 kg
- Znom (ohms) 8
- Revc (ohms) 6.83
- Sd (Square Meters) 0.084
- BL (T/M) 20.13
- Fo (Hz) 47.8
- Vas (liters) 162.6
- Mms (gm) 68.40
- Qms 5.23
- Qes 0.346
- Qts 0.325
- Xmax (mm) 2.6
- Le (mH) 0.32
- SPL (1W 1m) 98.9
- No (%) 4.97%
- Vd (cu. in. / ml) 13.3 / 218
- Pmax (Watts pgm.) 700
- Disp (cu. in. / ml) 197/ 3229
- Cms (uM/N) 162.3
- 15"
- Weight Unpacked: 16.98 lb(7.7 kg)
- Weight Packed: 18.08 lb(8.2 kg)
- Width Packed: 17.52"(44.5008 cm)
- Height Packed: 18.307"(46.49978 cm)
- Depth Packed: 7.087"(18.00098 cm)