

1208-4 SPS BWX™

OVERVIEW

1208-4 SPS BWX™

FEATURES

- Impedance: 4 Ohms
- Power capacity: 2000 W Peak 1000 W Program 500 W Continuous
- Sensitivity: 96.6 dB / 1 W 1 m
- Usable freq. range: 50 Hz ~ 3.5 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 16 lbs. / 7.3 kg
- Znom (ohms) 4
- Revc (ohms) 3.47
- Sd (Square Meters) 0.052
- BL (T/M) 14.09
- Fo (Hz) 55.4
- Vas (liters) 66.2
- Cms (uM/N) 172.5
- Mms (gm) 47.90
- Qms 7.09
- Qes 0.311
- Qts 0.298
- Xmax (mm) 2.3
- Le (mH) 0.19
- SPL (1W 1m) 96.6
- No (%) 2.90%
- Vd (cu. in. / ml) 18.4 / 302
- Pmax (Watts pgm.) 1000
- Disp (cu. in. / ml) 109 / 1797
- 12"
- Weight Unpacked: 16.00 lb(7.257 kg)
- Weight Packed: 18.50 lb(8.391 kg)
- Width Packed: 15.25"(38.735 cm)
- Height Packed: 16"(40.64 cm)
- Depth Packed: 6.5"(16.51 cm)