

# Sheffield® Pro 1500+™

## OVERVIEW

Sheffield® Pro 1500+™

## FEATURES

- 15"
- R<sub>vc</sub> (ohms) 5.12
- S<sub>d</sub> (Square Meters) 0.089
- BL (T/M) 14.18
- Z<sub>nom</sub> (ohms) 8
- V<sub>as</sub> (liters) 212.5
- C<sub>ms</sub> (uM/N) 190.2
- M<sub>ms</sub> (gm) 73.21
- Q<sub>ms</sub> 6.69
- Q<sub>es</sub> 0.500
- Net weight lb. / kg: 12.5 lbs. / 5.7 kg
- Q<sub>ts</sub> 0.465
- Voice coil material: 2 layers, thermally bonded copper wire Kapton former Nomex® stiffener
- X<sub>max</sub> (mm) 3.6
- Voice coil diameter: 2.5" / 63 mm
- L<sub>e</sub> (mH) 0.33
- Cone: Kevlar® impregnated cellulose
- SPL (1W 1m) 98.0
- Usable freq. range: 40 Hz ~ 3 kHz
- No (%) 3.20%
- Sensitivity: 98.0 dB / 1 W 1 m
- V<sub>d</sub> (cu. in. / ml) 36.2/593.3
- Power capacity: 1000 W Peak 500 W Program 250 W Continuous
- P<sub>max</sub> (Watts pgm.) 500
- Impedance: 8 Ohms
- Disp (cu. in. / ml) 196/ 3212
- F<sub>o</sub> (Hz) 42.7
- Weight Unpacked: 11.51 lb(5.22 kg)
- Weight Packed: 14.02 lb(6.36 kg)
- Width Packed: 7.62"(19.3548 cm)
- Height Packed: 16.62"(42.2148 cm)
- Depth Packed: 16.37"(41.5798 cm)