

15" Pro Rider® CU CP Subwoofer

OVERVIEW

15" Pro Rider® CU CP Subwoofer

FEATURES

- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Sensitivity: 97.9 dB / 1W 1m
- Net weight lb. / kg: 18 lbs./ 8.2 kg
- Znom (ohms) 8
- Revc (ohms) 5.70
- Usable freq. range: 35 Hz ~ 2 kHz
- Impedance: 8 Ohms
- Fo (Hz) 34.8
- 15"
- Cms (uM/N) 207.6
- Mms (gm) 100.50
- Qms 8.78
- Qes 0.242
- Qts 0.235
- Xmax (mm) 4.6
- Le (mH) 0.51
- SPL (1W 1m) 97.9
- No (%) 3.50%
- Vd (cu. in. / ml) 47.1 / 773
- Power capacity: 2400 W Peak 1200 W Program 600 W Continuous
- Disp (cu. in. / ml) 209 / 3426
- Sd (Square Meters) 0.084
- Voice coil material: Copper ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener
Solderless diffusion welded OFHC copper leads
- Pmax (Watts pgm.) 1200
- BL (T/M) 22.70
- Vas (liters) 208.0
- Weight Unpacked: 16.98 lb(7.7 kg)
- Weight Packed: 18.08 lb(8.2 kg)
- Width Packed: 17.52"(44.5008 cm)
- Height Packed: 18.307"(46.49978 cm)
- Depth Packed: 7.087"(18.00098 cm)