

15" Pro Rider® AL CP Subwoofer

OVERVIEW

15" Pro Rider® AL CP Subwoofer

FEATURES

- Impedance: 8 Ohms
- Power capacity: 2400 W Peak 1200 W Program 600 W Continuous
- Sensitivity: 96.3 dB / 1W 1m
- Usable freq. range: 35 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 4.0" / 100 mm
- Voice coil material: Aluminum ribbon wire Polyimide-impregnated fiberglass former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 18 lbs. / 8.2 kg
- Znom (ohms) 8
- Revc (ohms) 5.80
- Sd (Square Meters) 0.084
- BL (T/M) 16.50
- Fo (Hz) 40.4
- Vas (liters) 188.2
- Cms (uM/N) 187.8
- Mms (gm) 82.50
- Qms 8.73
- Qes 0.450
- Qts 0.428
- Xmax (mm) 4.6
- Le (mH) 0.41
- SPL (1W 1m) 96.3
- No (%) 2.70%
- Vd (cu. in. / ml) 47.1 / 773
- Pmax (Watts pgm.) 1200
- Disp (cu. in. / ml) 209 / 3426
- 15"
- Weight Unpacked: 16.98 lb(7.7 kg)
- Weight Packed: 18.08 lb(8.2 kg)
- Width Packed: 17.52"(44.5008 cm)
- Height Packed: 18.307"(46.49978 cm)
- Depth Packed: 7.087"(18.00098 cm)