

Scorpion® SP-15825 8 Ohm

OVERVIEW

Scorpion® SP-15825 8 Ohm

FEATURES

- 15"
- Impedance: 8 Ohms
- Power capacity: 800 W Peak 400 W Program 200 W Continuous
- Sensitivity: 98.7 dB / 1 W 1 m
- Usable freq. range: 40 Hz ~ 2 kHz
- Cone: Kevlar® impregnated cellulose
- Voice coil diameter: 2.5" / 64 mm
- Voice coil material: Aluminum ribbon wire Kapton former Nomex® stiffener Solderless diffusion welded OFHC copper leads
- Net weight lb. / kg: 12.75 lbs. / 5.8 kg
- Znom (ohms) 8
- Revc (ohms) 5.54
- Sd (Square Meters) 0.084
- BL (T/M) 17.10
- Fo (Hz) 50.1
- Vas (liters) 132.4
- Cms (uM/N) 174.5
- Mms (gm) 70.30
- Qms 6.05
- Qes 0.345
- Qts 0.326
- Xmax (mm) 3.1
- Le (mH) 0.3
- SPL (1W 1m) 98.7
- No (%) 4.70%
- Vd (cu. in. / ml) 13.9 / 227
- Pmax (Watts pgm.) 400
- Disp (cu. in. / ml) 201/ 3294
- Weight Unpacked: 17.42 lb(7.9 kg)
- Weight Packed: 22.27 lb(10.1 kg)
- Width Packed: 17.52"(44.5008 cm)
- Height Packed: 18.307"(46.49978 cm)
- Depth Packed: 7.087"(18.00098 cm)