

44XT™ w/ adapter Driver

OVERVIEW

44XT™ w/ adapter Driver

FEATURES

- 4"
- Throat Parameter: Standard: 2" / 50.8 mm
- Optional: 1.6" / 40.6 mm Supplied with throat extension
- Nominal Impedance: 8 Ohms
- Minimum Impedance: 7.1 Ohms
- DC Resistance: 6.8 Ohms
- Power Capacity 1000 Hz to 20,000 Hz: 400 W peak 200 W program 100 W continuous using pink noise band limited from 1,000 Hz to 20 kHz (AES 2-1984)
- Power Capacity 500 Hz to 20,000 Hz: 320 W peak 160 W program 80 W continuous
- Sensitivity: 111 dB SPL 1 Watt at 1 meter On-axis on a 80° H x 40° V horn
- Nominal Efficiency: 30%
- Frequency Response: 500 Hz to 20,000 Hz
- Recommended Crossover: 1,000 Hz
- Lowest Recommended Crossover: 500 Hz at 12 dB / Octave
- Diaphragm: Commercially pure titanium
- Voice Coil Diameter: 4" / 101 mm
- Voice Coil Material: Edge-wound aluminum ribbon with a composite bobbin
- Flux Density: 19,000 gauss (1.9T)
- Dimensions: Standard: 8.388" (213 mm)D x 6.05: (154 mm) H
- Net Weight: Standard: 21 lbs. / 9.5 kg
- Shipping Weight: Standard: 25 lbs. / 11.4 kg
- Weight Unpacked: 21.61 lb(9.8 kg)
- Weight Packed: 24.69 lb(11.2 kg)
- Width Packed: 12"(30.48 cm)
- Height Packed: 12.25"(31.115 cm)
- Depth Packed: 8.5"(21.59 cm)